

## Product Data Sheet

**Model Name: PDU-1606B-UK**

(220~250V, 50/60 Hz, 6xUK Outlets, 19")

**Product Description** High-end power distribution in a compact design for IT network and server racks.

### Output

Nominal Output Voltage 220~250V

Maximum Total Current Draw per Phase 16A

Output Connections 6 X BS 1363 OUTLETS,

### Input

Nominal Input Voltage 220~250V

Input Frequency 50-60 HZ

Input Connection IEC 60309 16A (2P+ $\neq$ )

Cord Size and Length 3C X 2.5 MM<sup>2</sup>, Length: 1.8 Metre / 3 Metre / 5 Metre (IEC 60227)

Maximum Input Current Per Phase 16A

Number of Power Cords 1

Load Capacity 4000 W MAX

### Overload Protection

Protection Type MCB 2P 16A

### Physical

Body Type Anodized Aluminium, Polycarbonate.

Maximum Height 482.6 mm

Maximum Width 49 mm

Maximum Depth 84 mm

Color Anodized Aluminium, Silver / Black,

Mount Type Non-Rotatable Metal Hanger



## Features

Master Switch MCB

---

Fire resistance Flame Retardant

---

## Environmental

Operating Temperature 0-45°C

---

Storage Temperature -25 - 65°C

---

Operating Relative Humidity 0-95%

---

## Conformance

Standard Warranty 3 Years Repair or Replace

---

## Standards

IEC 60309 Plugs, And Socket Outlets for Industrial Purposes

BS 1363 Plugs and Socket-Outlets for Household and Similar Purposes.

---

## Certifications



---

Earth Connection is Must Before Connecting to the Power Supply