

Product Data Sheet

Model Name: PDU 820 6 WAY UK STD 19"

(220~250, 50/60 Hz, 6 UK)

موزع كهربيائي 6 منافذ UK 13 امبير 19 انش قابس BS 1363

Product Description High-end power distribution in a compact design for IT network and server racks.

Output

Nominal Output Voltage 220~250V

Maximum Total Current Draw per Phase 13A

Output Connections 6 X BS 1363 OUTLETS

Input

Nominal Input Voltage 220~250V

Input Frequency 50-60 HZ

Input Connection BS 1363 PLUG

Cord Size and Length 3C X 1.5MM², Length:1.8 Metre / 3 Metre / 5 Metre

Maximum Input Current Per Phase 13A

Number of Power Cords 1

Load Capacity 3250 W MAX

Overload Protection

Protection Type **Push-button Reset Overload Protector - 13A**

Physical

Body Type Polyvinyl Chloride, Polycarbonate.

Maximum Height 482 mm

Maximum Width 49 mm

Maximum Depth 84 mm

Color Black, Yellow

Mount Type 360° Rotatable Hanger

FEB/2022



Features

Master Switch Double Pole Rocker Switch (On/Off) With LED Indicator

Fire resistance Flame Retardant

Environmental

Operating Temperature 0-45^oc

Storage Temperature -25 - 65^oc

Operating Relative Humidity 0-95%

Conformance

Standard Warranty 3 Years Repair or Replace

Standards

SASO 2815 Safety Requirements for Cord Extension Sets

BS 1363 Plugs and Socket-Outlets for Household and Similar Purposes.

Certifications



Earth Connection is Must Before Connecting to the Power Supply