

## Product Data Sheet

**Model Name: PDU-1606B-C13 (UK)**

(220~250, 50/60 Hz, 06 C13)

<b>Product Description</b>	High-end power distribution in a compact design for IT network and server racks.
<b>Output</b>	
Nominal Output Voltage	220~250V
Maximum Total Current Draw per Phase	13A
Output Connections	06 X IEC - C13 OUTLETS
<b>Input</b>	
Nominal Input Voltage	220~250V
Input Frequency	50-60 HZ
Input Connection	UK PLUG (FUSED)
Cord Size and Length	3C X 1.5 MM <sup>2</sup> , Length: 1.8 Metre / 3 Metre / 5 Metre (IEC 60227)
Maximum Input Current Per Phase	13A
Number of Power Cords	1
Load Capacity	3250 W MAX
<b>Overload Protection</b>	
Protection Type	Overload Protection 13A
<b>Physical</b>	
Body Type	Anodized Aluminium, Polycarbonate.
Maximum Height	482mm
Maximum Width	49 mm
Maximum Depth	84 mm
Color	Anodized Aluminium, Silver/ Black,
Mount Type	1U Hanger / Non-Rotatable



## Features

Master Switch Double Pole Switch (16A)

---

Fire resistance Flame Retardant

---

## Environmental

Operating Temperature 0-45°C

---

Storage Temperature -25 - 65°C

---

Operating Relative Humidity 0-95%

---

## Conformance

Standard Warranty 3 Years Repair or Replace

---

## Standards

BS 1363 UK Plug and Sockets

IEC 60320 C13 / C19 Connectors

---

## Certifications



---

Earth Connection is Must Before Connecting to the Power Supply

Actual Product May Vary from The Photo