

Product Data Sheet

Model Name: PDU-1610B-UK

(220~250, 50/60 Hz, 10 UK, 0U)

Product Description High-end power distribution in a compact design for IT network and server racks.

Output

Nominal Output Voltage 220~250V

Maximum Total Current Draw per Phase 16A

Output Connections 10 X BS 1363 OUTLETS

Input

Nominal Input Voltage 220~250V

Input Frequency 50-60 HZ

Input Connection IEC 60309 16A (2P+ \neq)

Cord Size and Length 3C X 2.5MM², Length: 1.8 Metre / 3 Metre / 5 Metre

Maximum Input Current Per Phase 16A

Number of Power Cords 1

Load Capacity 4000 W MAX

Overload Protection

Protection Type Double Pole MCB C16 (16A)

Physical

Body Type Anodized Aluminium, Polycarbonate.

Maximum Height 860 mm

Maximum Width 49 mm

Maximum Depth 84 mm

Color Anodized Aluminium, Black, Yellow

Mount Type 360° Rotatable Hanger



Features

Master Switch 2P MCB Control

Fire resistance Flame Retardant

Environmental

Operating Temperature 0-45^oc

Storage Temperature -25 - 65^oc

Operating Relative Humidity 0-95%

Conformance

Standard Warranty 3 Years Repair or Replace

Standards

IEC 60309 Plugs, And Socket Outlets for Industrial Purposes

BS 1363 Plugs and Socket-Outlets for Household and Similar Purposes.

Certifications



Earth Connection is Must Before Connecting to the Power Supply