

Product Data Sheet

Model Name: PDU-3212B-C13

(220~250V, 50/60 Hz, 12 X C13,0U)

Product Description High-end power distribution in a compact design for IT network and server racks.

Output

Nominal Output Voltage 220~250V 50/60 Hz

Maximum Total Current Draw per Phase 32A

Output Connections 12 X C13 OUTLETS

Input

Nominal Input Voltage 220~250V 50/60 Hz

Input Frequency 50-60 HZ

Input Connection IEC 60309 32A (2P+ ≐)

Cord Size and Length 3C X 4 MM², Length: 1.8 Metre / 3 Metre /5 Metre (IEC 60227)

Maximum Input Current Per Phase 32A

Number of Power Cords 1

Load Capacity 8000 W MAX

Overload Protection

Protection Type Double Pole MCB 32A

Physical

Body Type Anodized Aluminium, Polycarbonate.

Maximum Height 700mm

Maximum Width 49 mm

Maximum Depth 84 mm

Color Anodized Aluminium, Black,

Mount Type Non-Rotatable Metal Hanger



Features

Master Switch 2P MCB Control

Fire resistance Flame Retardant

Environmental

Operating Temperature 0-45°C

Storage Temperature -25 - 65°C

Operating Relative Humidity 0-95%

Conformance

Standard Warranty 3 Years Repair or Replace

Standards

IEC 60309 Plugs, And Socket Outlets for Industrial Purposes

IEC 60320 C13 & C19 Connectors

Certifications



Earth Connection is Must Before Connecting to the Power Supply